

SKG productcertificate

437.153.01

date of issue: 24-02-2014



Certificateholder
Wilka Schließtechnik GmbH
Mettmanner Straße 56-64
D-42549 Velbert
T : +49 (0) 2051 208 10
F : +49 (0) 2051 208 1151
E : info@wilka.de
I : www.wilka.de



Declaration of SKG

This certificate is in accordance with the SKG Regulations approval, product certification and process certification: 2011.

SKG declares that the by or on behalf of the certificate owner produced building hardware product:
lock with swingbolt

delivered under logo / brand:
WILKA / DLC / MARENCO

delivered under type- and / or article number:
1735 , 1736

meets class 2 STER according BRL 3104 and NEN 5089: 2009 if the product is indelibly marked with the SKG mark, as shown above.

SKG

bezoekadres
Nieuwe Kanaal 9F
6709 PA Wageningen

postadres
Postbus 362
6700 AJ Wageningen

T 0317 - 421 720
F 0317 - 421 677
E info@skg.nl
I www.skg.nl

For SKG

ir. H.A.J. van Dartel
Certification manager

Verify at www.sterrenwijzer.nl if this certificate is still valid and actual.

This certificate has 2 pages

SKG productcertificate

Wilka Schließtechnik GmbH

Number: 437.153.01

page 2 of 2

1. PRODUCT

lock with swingbolt

MAIN GROUP

single lock

2. TECHNICAL SPECIFICATION:

Construction: 1 forend with lockcase with turning bolt with or without gap, without latch

Operating / System: with 17 mm profile cylinder; BS: 25/30/35/40 mm

Material: forend: inox, lockcase: steel zinc coated

Dimension: forend: 245x28x4 mm; lockcase: 180xBS+15x16 mm

Fixing: forend: 2 point; forend: 4 point

Intended use: for left or right opening metal doors

3. DELIVERY

The delivery includes an installation instruction:

70 40 001 05/2004

4. PERFORMANCES

A lock with swingbolt according this certificate fulfils the relevant requirements of BRL 3104.

A window- or door set, in which this lock with swingbolt is installed according the installation instructions of the certificate holder meets at least burglar resistance class (RC) 2 of NEN 5096 and EN 1627, if:

- the façade element or the (profile-)system from which the element is manufactured is delivered under a (KOMO-)quality approval with respect to the aspect burglar resistance, in which the actual window or door type is admitted and the herein mentioned conditions are fulfilled. Remark: In façade elements in accordance with a burglar resistance class (RC) of EN 1627 only SKG*** cylinders are applicable.

A window or door, in existing buildings, in which this lock with swingbolt is installed according the installation instructions of the certificate holder, meets the requirements of the Police Mark Save Housing (PKVW) - Existing Building, if:

- the other aspects of the façade element also comply with the applicable PKVW Protection directive (publication CCV).
-