

SKG-IKOB PRODUCTCERTIFICATE

437.612.03

Date of issue: 29-09-2016



Certificate holder

Wilka Schließtechnik GmbH
Mettmanner Straße 56-64
D-42549 Velbert
T: +49 (0) 2051 208 10
E: info@wilka.de
I: www.wilka.de



Declaration of SKG-IKOB

This certificate has been issued on the basis of BRL 3104 in accordance with the SKG-IKOB Regulations for Attestation, Certification and Inspection.

SKG-IKOB declares that the by or on behalf of the certificate owner produced building hardware product:

keeper

delivered under logo / brand:

WILKA / DLC / MARENCO

delivered under type- and / or article number:

10 26 669

meets class 2 STER according BRL 3104 and NEN 5089: 2009 if the product is indelibly marked with the SKG mark, as shown above.

For SKG-IKOB

A handwritten signature in blue ink, consisting of a series of loops and a long horizontal stroke extending to the right.

ir. H.A.J. van Dartel
Certification manager

Verify at www.sterrenwijzer.nl if this certificate is still valid and actual.
This certificate contains 2 pages.

CERTIFICATE

SKG-IKOB Certificatie
Poppenbouwing 56
4191 NZ Geldermalsen

Postbus 202
4190 CE Geldermalsen

T 088-2440100
info@skgikob.nl
www.skgikob.nl

SKG-IKOB PRODUCTCERTIFICATE

Wilka Schließtechnik GmbH
Number: 437.612.03

page 2 of 2

1. PRODUCT

keeper

MAIN GROUP

single lock

2. TECHNICAL SPECIFICATION:

Construction: 1 keeperplate

Operating / System: single hole for latch

Material: plate: inox

Dimension: strip: 245x28x4 mm

Fixing: 4 point Ø 5 mm

Intended use: metal, door-inward-opening, door-outward-opening
for metal doors in combination with narrow lock (cert.nr. 417.153.01)

3. DELIVERY

The delivery includes an installation instruction:
70 40 507 9.16

4. PERFORMANCES

A keeper according this certificate fulfils the relevant requirements of BRL 3104.

A window- or door set, in which this keeper is installed according the installation instructions of the certificate holder meets at least burglar resistance class (RC) 2 of NEN 5096 and EN 1627, if:

- the façade element or the (profile-)system from which the element is manufactured is delivered under a (KOMO-)quality approval with respect to the aspect burglar resistance, in which the actual window or door type is admitted and the herein mentioned conditions are fulfilled. Remark: In façade elements in accordance with a burglar resistance class (RC) of EN 1627 only SKG*** cylinders are applicable.

A window or door, in existing buildings, in which this keeper is installed according the installation instructions of the certificate holder, meets the requirements of the Police Mark Save Housing (PKVW) - Existing Building, if:

- the other aspects of the façade element also comply with the applicable PKVW Protection directive (publication CCV).
-