

SKG-IKOB PRODUCTCERTIFICATE

437.612.04

Date of issue: 29-01-2020



Certificate holder

Wilka Schließtechnik GmbH
Mettmanner Straße 56-64
D-42549 Velbert
T: +49 (0) 2051 208 10
E: info@wilka.de
I: www.wilka.de



Declaration of SKG-IKOB

This certificate has been issued on the basis of BRL 3104 in accordance with the SKG-IKOB Regulations for Attestation, Certification and Inspection.

SKG-IKOB declares that the by or on behalf of the certificate owner produced building hardware product:

keeper plate

delivered under logo / brand:

WILKA

delivered under type- and / or article number:

P641/P643/P703/P747

meets class 2 STER according BRL 3104 and NEN 5089: 2009 if the product is indelibly marked with the SKG mark, as shown above.

For SKG-IKOB

A blue ink handwritten signature, appearing to be "H.A.J. van Dartel", written over a horizontal line.

ir. H.A.J. van Dartel
Certification manager

Verify at www.sterrenwijzer.nl if this certificate is still valid and actual.
This certificate contains 2 pages.

CERTIFICATE

SKG-IKOB Certificatie
Poppenbouwing 56
4191 NZ Geldermalsen

Postbus 202
4190 CE Geldermalsen

T 088-2440100
info@skgikob.nl
www.skgikob.nl

SKG-IKOB PRODUCTCERTIFICATE

Wilka Schließtechnik GmbH
Number: 437.612.04

page 2 of 2

1. PRODUCT
keeper plate

PRODUCT TYPE
lock striker plate

2. TECHNICAL SPECIFICATION

Operating: N.A.
Construction: 1 keeper plate
System: double hole
Material: plate: stainless steel
Dimension: plate:
F: 245~380x24x3,0 mm
U: 245~380x24x6,0 mm
Fixing: 245 mm: 3 punts Ø 5,5 mm h.o.h. 94,5/127 mm
380 mm: 3 punts Ø 5,5 mm h.o.h. 162/193 mm
Intended use: metal, door-inward-opening, door-outward-opening
in metal doors in combi with WILKA cylinder-mortice anti-panik narrow lock
(certificate 437.112.04)

3. DELIVERY

The delivery includes an installation instruction:
70_40_584-001_P641_643_703_747_SKG

4. PERFORMANCES

A keeper plate according this certificate fulfils the relevant requirements of BRL 3104.

A window- or door set, in which this keeper plate is installed according the installation instructions of the certificate holder meets at least burglar resistance class (RC) 2 of NEN 5096 and EN 1627, if:

- the façade element or the (profile-)system from which the element is manufactured is delivered under a (KOMO-)quality approval with respect to the aspect burglar resistance, in which the actual window or door type is admitted and the herein mentioned conditions are fulfilled.

A window or door, in existing buildings, in which this keeper plate is installed according the installation instructions of the certificate holder, meets the requirements of the Police Mark Save Housing (PKVW) - Existing Building, if:

- the other aspects of the façade element also comply with the applicable PKVW Protection directive (publication CCV).
-