SKG-IKOB PRODUCTCERTIFICATE 437.142.01

Date of issue: 02-12-2015





Certificate holder

Wilka Schließtechnik GmbH Mettmanner Straße 56-64 D-42549 Velbert

T: +49 (0) 2051 208 10 F: +49 (0) 2051 208 1151

E: info@wilka.de I: www.wilka.de

Declaration of SKG-IKOB

This certificate has been issued on the basis of BRL 3104 in accordance with the SKG Regulations approval, product certification and process certification: 2011.

SKG-IKOB declares that the by or on behalf of the certificate owner produced building hardware product:

lock for profiles

delivered under logo / brand:

WILKA / DLC / MARENCO

delivered under type- and / or article number:

1738

meets class 2 STER according BRL 3104 and NEN 5089: 2009 if the product is indelibly marked with the SKG mark, as shown above.

For SKG-IKOB

ir. H.A.J. van Dartel Certification manager

Verify at www.sterrenwijzer.nl if this certificate is still valid and actual. This certificate contains 2 pages.

SKG-IKOB Certificatie Poppenbouwing 56 4191 NZ Geldermalsen

Postbus 202 4190 CE Geldermalsen

T 088-2440100 info@skgikob.nl www.skgikob.nl

SKG-IKOB PRODUCTCERTIFICATE

Wilka Schließtechnik GmbH

Number: 437.142.01 page 2 of 2

1. PRODUCT MAIN GROUP lock for profiles single lock

2. TECHNICAL SPECIFICATION:

Construction: 1 forend with lockcase with latch and square bolt

Operating / System: with 17 mm profile cylinder; PZ: 92 mm; BS: 25 to 45 mm

Material: forend: inox, lockcase: steel zinc coated

Dimension: lockcase: 178xBS+15x15 mm; forend: 245x24x3 mm OR 380x24x3 mm

Fixing: forend: 2 point

Intended use: metal, door-inward-opening, door-outward-opening

for left or right opening metal doors

3. DELIVERY

The delivery includes an installation instruction:

70 40 501 11.15

4. PERFORMANCES

A lock for profiles according this certificate fulfils the relevant requirements of BRL 3104.

A window- or door set, in which this lock for profiles is installed according the installation instructions of the certificate holder meets at least burglar resistance class (RC) 2 of NEN 5096 and EN 1627, if:

• the façade element or the (profile-)system from which the element is manufactured is delivered under a (KOMO-)quality approval with respect to the aspect burglar resistance, in which the actual window or door type is admitted and the herein mentioned conditions are fulfilled. Remark: In façade elements in accordance with a burglar resistance class (RC) of EN 1627 only SKG*** cylinders are applicable.

A window or door, in existing buildings, in which this lock for profiles is installed according the installation instructions of the certificate holder, meets the requirements of the Police Mark Save Housing (PKVW) - Existing Building, if:

• the other aspects of the façade element also comply with the applicable PKVW Protection directive (publication CCV).