

SKG-IKOB PRODUCTCERTIFICATE

437.112.02

Date of issue: 11-03-2020



Certificate holder

Wilka Schließtechnik GmbH
Mettmanner Straße 56-64
D-42549 Velbert
T: +49 (0) 2051 208 10
E: info@wilka.de
I: www.wilka.de



Declaration of SKG-IKOB

This certificate has been issued on the basis of BRL 3104 in accordance with the SKG-IKOB Regulations for Attestation, Certification and Inspection.

SKG-IKOB declares that the by or on behalf of the certificate owner produced building hardware product:

cylinder-mortice anti-panik narrow lock

delivered under logo / brand:

WILKA

delivered under type- and / or article number:

**7667 , 7668 , 7677 , 7678 , 7687 , 7688
767Z , 768Z , 777Z , 778Z , 787Z , 788Z**

meets class 2 STER according BRL 3104 and NEN 5089: 2009 if the product is indelibly marked with the SKG mark, as shown above.

(at which the symbol for escape doors or the code EN179/EN1125 is added.)



For SKG-IKOB

A blue ink handwritten signature, appearing to be "H.A.J. van Dartel", written over a light blue horizontal line.

ir. H.A.J. van Dartel
Certification manager

Verify at www.sterrenwijzer.nl if this certificate is still valid and actual.
This certificate contains 2 pages.

SKG-IKOB Certificatie
Poppenbouwing 56
4191 NZ Geldermalsen

Postbus 202
4190 CE Geldermalsen

T 088-2440100
info@skgikob.nl
www.skgikob.nl

CERTIFICATE

SKG-IKOB PRODUCTCERTIFICATE

Wilka Schließtechnik GmbH
Number: 437.112.02

page 2 of 2

1. PRODUCT

cylinder-mortice anti-panik narrow lock

PRODUCT TYPE

single lock

2. TECHNICAL SPECIFICATION

Operating:	Mechanical operation
Construction:	1 forend with lock case, with latch and selflocking deadbolt
System:	with 17 mm profile cylinder PZ: 92 mm BS: 35 ~ 45 mm
Material:	forend: stainless steel lockcase: steel zinc coated
Dimension:	forend: F: 245~380x24x3,0 mm U 245~380x24x6,0 mm
Fixing:	lock case: 183,5 x(BS+15 mm) x 15,5 mm forend: 2 point M5
Intended use:	metal, door-inward-opening, door-outward-opening in metal doors in combi with WILKA keeper plate (certificate 437.612.04)

3. DELIVERY

The delivery includes an installation instruction:
70_40_583-001_Serie_7000_SKG

4. PERFORMANCES

A cylinder-mortice anti-panik narrow lock according this certificate fulfils the relevant requirements of BRL 3104.

A window or door, in existing buildings, in which this cylinder-mortice anti-panik narrow lock is installed according the installation instructions of the certificate holder, meets the requirements of the Police Mark Save Housing (PKVW) - Existing Building, if:

the other aspects of the façade element also comply with the applicable PKVW Protection directive (publication CCV).
